Minimum Load Requirements for Cylindrical Roller Bearings

In order to prevent roller skidding, a common failure in Cylindrical Roller Bearings (CRB), loads must be applied to CRB type roller bearings during operation (or testing). Skidding can occur even in very short periods of time without proper loading, reducing the bearing's life. Please refer to the charts below for the minimum required loads for 200 and 300 series CRB's (NU204-NU338). The minimum required load is calculated based on the bearing size, bearing limiting speed, operating speed and mean pitch diameter.

000 1000 1000 0000

	900	1200	1800	3600			
	rpm	rpm	rpm	rpm			
Base Part							
Number	Force (lbs)						
NU204	23	24	24	26			
NU205	31	31	32	34			
NU206	45	45	47	51			
NU207	59	61	63	69			
NU208	77	79	82	90			
NU209	91	93	97	108			
NU210	107	110	114	129			
NU211	131	134	140	159			
NU212	161	165	173	199			
NU213	190	195	206	239			
NU214	211	218	230	268			
NU215	235	242	257	301			
NU216	274	283	301	356			
NU217	314	326	348	416			
NU218	357	370	397	478			
NU219	404	420	452	549			
NU220	453	472	510	623			
NU221	510	533	578	714			
NU222	569	595	648	807			
NU224	681	719	795	1022			
NU226	778	819	901	1147			
NU228	929	982	1088	1406			
NU230	1091	1157	1289	1685			
NU232	1270	1352	1516	2008			
NU234	1470	1571	1774	2382			
NU236	1610	1724	1954	2644			

NU238 | 1847 | 1989 | 2273 | 3126 |

	900	1200	1800	3600			
	rpm	rpm	rpm	rpm			
Base Part							
Number	Force (lbs)						
NU304	28	28	29	31			
NU305	41	41	43	46			
NU306	57	58	60	66			
NU307	70	71	74	82			
NU308	93	94	98	110			
NU309	114	117	122	137			
NU310	140	143	150	171			
NU311	169	173	182	210			
NU312	200	206	217	252			
NU313	235	242	257	301			
NU314	272	281	299	354			
NU315	313	324	346	413			
NU316	357	370	397	478			
NU317	400	415	447	541			
NU318	453	472	510	623			
NU319	506	528	572	704			
NU320	583	610	665	827			
NU321	645	677	740	929			
NU322	732	770	845	1070			
NU324	877	925	1023	1315			
NU326	1039	1102	1228	1606			
NU328	1214	1293	1449	1919			
NU330	1409	1506	1700	2283			
NU332	1610	1724	1954	2644			
NU334	1847	1989	2273	3126			
NU336	2087	2254	2588	3590			
NU338	2348	2543	2935	4109			





- Ratings are applicable for all CRB Series N, NU, NJ
- Contact Koyo's Application
 Engineering Department to
 determine minimum loads for
 bearings that fall outside of the
 size range provided in the chart.
- Please refer to Koyo's AMD Program Price Book for a list of Koyo's current CRB offering.